


## 抗阻塞滲透陰井螺紋網管(WSO)-規格表



螺紋滲透陰井同徑平接頭規格表

標稱管徑		內徑*外徑 ±3.0%mm	螺距 ±3.0%mm	長度 m
英吋	型號			
4"	WSO-100A	98*114	12.5mm	5m
5"	WSO-125A	123*140	14.0mm	5m
6"	WSO-150A	148*165	14.0mm	5m
8"	WSO-200A	195*216	14.5mm	5m
10"	WSO-250A	239*267	14.5mm	5m
12"	WSO-300A	290*318	15.0mm	5m
16"	WSO-400A	390*420	15.5mm	5m

標稱管徑		內徑*外徑 ±3.0%mm	螺距 ±3.0%mm	長度 cm
型號	型號			
4" <b>F</b>	WSF-100A	115.0x130.0	12.5mm	30cm
5" <b>F</b>	WSF-125A	141.0x160.0	14.0mm	30cm
6" <b>F</b>	WSF-150A	166.0x183.0	14.5mm	35cm
8" <b>F</b>	WSF-200A	217.0*240.0	14.5mm	40cm
10" <b>F</b>	WSF-250A	268.0*290.0	14.5mm	45cm
12" <b>F</b>	WSF-300A	320.0*342.0	15.0mm	50cm
16" <b>F</b>	WSF-400A	422.0*452.0	15.5mm	55cm



- 管壁高密度網孔設計
- 管壁T型螺紋環繞，抗壓性高，抗阻塞。
- 螺紋陰井網管防沙土進入管內的結構設計，不需不織布等過濾材料包管，網管抗阻塞。

